



Pressure transducers DMU 30

Part no. DMU 30211210202

Pressure transducer industrial version

benefits

- for pressure ranges up to 1,000 bar
- suitable for high overloads
- insensitive to pressure peaks
- Ex version (optional)

Application

For electronic pressure measurement in machines and systems with technical gases (e.g. oxygen, oil-free, grease-free) and for use in hydrogen applications.

Description

Pressure transducers convert physical pressure into an electrical signal proportional to the pressure. DMU 30 is equipped with a welded stainless steel measuring cell.

Technical Specifications

Measuring accuracy

Deviation from the characteristic curve according to IEC 60770 – limit point calibration (non-linearity, hysteresis, repeatability)
 $< \pm 0.5 \% \text{ FSO}$

Long-term stability

$\leq \pm 0.2 \% \text{ FSO/year}$ at reference conditions

Measuring range

0/250 bar

Overpressure safety

$> 16 \text{ bar}$
 $2 \times \text{FS}$

Burst pressure

$< 600 \text{ bar}$
 at least $5 \times \text{FS}$
 Vacuum resistance: unlimited

Operating temperature range

Medium: -40/+125 °C
 Ambient: -40/+100 °C
 in Ex zZone 0: -20/+60 °C
 from Ex zone 1: -20/+70 °C
 Storage: -40/+85 °C

Temperature error band

$\leq \pm 0.2 \% \text{ FSO}/10 \text{ K}$ In compensated range -25/+85 °C

dynamic characteristics

Response time: $\leq 10 \text{ ms}$

Process connection

G $\frac{1}{4}$ B (EN 837-1/7.3)

material

Housing: Stainless steel 316 L
 pressure connection: Stainless steel 316 L
 diaphragm: Stainless steel 316 L
 Seal: without (welded)
 Degree of cleanliness: oil- and grease-free version, based on ISO 15001
 Residual particles: no particles > 100 μm (with reference to 10 dm^2)
 Residual grease: Residual grease content < 0.2 mg/dm^2

Supply voltage

Ex version
 DC 10 – 28 V

Output signal

4–20 mA, 2-wire

Load

$R_{\text{max}} = [(UB - UB_{\text{min}})/0.02 \text{ A}] \Omega$

Current input

< 25 mA

electrical protection

short circuit proof and protected against reverse polarity

Electrical connection

Cable outlet with PVC cable

Degree of protection

IP 67 (EN 60529)


CE conformity

EMC Directive 2014/30/EU
 RoHS Directive 2011/65/EU
 Pressure Equipment Directive 2014/68/EU

Options

- Ex version zone 0+20 (II 1G Ex ia IIC T4 Ga, II 1D Ex ia IIIC T135 °C Da)
- other electrical connections
- Other output signal
- Fitting of chemical seal

Technical Drawings



Versions

			Connection	Connection	Measuring range		Part no.
	Cable outlet with PVC cable	Ex version	G¼B	(EN 837-1/7.3)	0/250 bar	●	DMU 30211210202

- in-stock items
- Non-stock items