




radiator lockshield valve 456 M E DN15

Part no. 453 220

radiator lockshield valve

benefits

- fully adjustable
- shutting off individual radiators
- reproducible adjustment

Application

To shut off individual radiators so that maintenance work or painting can be performed without having to drain the entire heating system. Suitable for medium water volumes. For installation in single-pipe and dual-pipe heating systems.

Description

Radiator lockshield valve type 456 with drain, shut-off and adjustment function. With cap (version M) to protect against incorrect operation. Adjustable according to flow diagram (see operating instructions). The selected setting is reproducible due to the integrated stroke limiter/stop (not version M Eco) and thus independent of draining. The optional filling and draining unit FEV with hose connection G $\frac{1}{2}$ can be used for easy and fast draining. Draining capacity equal to flow coefficient 1.1. Versions M Eco without stroke limiter.

Technical Specifications

System connection

see ordering table

adjustment range at 10 kPa

405 l/h

Nominal pressure

max. 10 bar

Nominal diameter

DN 15

Operating temperature range


Medium: max. 120 °C

Housing

Gunmetal, nickel-plated

Technical Drawings

type 456 M – angled



DN	D	d2	SW1	SW2	b	L1	L2	L3	L4	L5	L8
10	Rp $\frac{3}{8}$	R $\frac{3}{8}$	22	27	10,1	49	75	26	52	22	22
15	Rp $\frac{1}{2}$	R $\frac{1}{2}$	27	30	13,2	51	80	29	58	26	22
20	Rp $\frac{3}{4}$	R $\frac{3}{4}$	32	37	14,5	59	91	34	66	29	22

Versions

		Version	Version	Nominal diameter	Conne- ction	Flow coef- ficient Kvs*		Part no.
	456 M	for medium water volu- mes	Angled	DN 15	Rp $\frac{1}{2}$ x R $\frac{1}{2}$	1.28 m ³ /h		453 220

-  in-stock items
-  Non-stock items