



Thermometers THK 150 S/58 S

Part no. 67542135S

Thermometers with capillary tube

benefits

- ideal for boilers and water heaters
- corrosion-resistant, highly impact-resistant plastic housing
- many customised versions available

Application

Heating and plumbing, e.g. boilers, water heaters, hot water storage tanks

Technical Specifications

Nominal size
25 mm x 58 mm

Range
0/120 °C

Measuring principle
Liquid filling

Operating temperature range
Medium: Full scale value
Ambient: max. 70 °C

Operating pressure
without pressure

Degree of protection
IP 32 (EN 60529)

Options

- Dial with customer logo
- various capillary lengths
- special colours for housing, dial, pointer

Connection

Probe: Ø 6.5 x 30 mm, Copper
Capillary tube: Copper with PVC coating (R3, grey)

Dial

Plastic, black
Scaling: white

Housing

Plastic (ABS), black

Bezel

THK 150 S/58 S

capillary length

2000 mm

Versions

| Nomi- nal size | Nomi- nal size | Hou- sing | push on bezel | Pointer | Dial | Scale | Range | capil- lary length | Type | Part no. |
|-------------------|-------------------|--------------|------------------|---------|-------|-------|-------------|--------------------------|----------------------|-------------|
| | 25 x 58 mm | black | | | black | white | 0/120 °C | 2000 mm | THK 150 S/58 S | ● 67542135S |

● in-stock items

● Non-stock items