



## Boiler manifold KSV 125-3 70 kW

Part no. 77311

Boiler manifold KSV 125 for heating pump assemblies PrimoTherm®

### benefits

- compact and robust version in form-fit insulation
- for two or three heating pump assemblies, with optional hydraulic separator
- 2 wall mounting bracket for easy mounting included
- AFRISO boiler manifolds are tightness-tested in the factory.

### Application

For distribution of the heating circuit water in sealed heating systems as per EN 12828 from the boiler to the heating pump assemblies PrimoTherm®.

### Description

Boiler manifold as combination flow and return manifold for two, three, four or five heating pump assemblies. AFRISO boiler manifolds are tightness-tested in the factory; they are maintenance-free.

### Technical Specifications

#### system connections

70 kW  
 threaded socket G1½ male  
 70 kW  
 union nut G1½, flat-sealing

#### Axis distance

125 mm

#### Operating temperature range

Medium: max. 110 °C

#### Flow

70 kW  
 3 m³/h

#### System pressure

max. 6 bar

#### Heat insulation

Polypropylene EPP

#### Scope of delivery

- Boiler manifold
- 2 x wall mounting bracket
- Insulation

## Versions

	Heating circuits	hydraulic separator		Part no.
Boiler manifold KSV 125-3 70 kW	3	0		77311

-  in-stock items
-  Non-stock items