



liquid detector AFA 11

Part no. 40890

liquid detector

benefits

- For storage rooms, manholes, collection facilities, etc.
- with visual and audible alarms
- Test/Acknowledge keys and relay output
- Self-monitoring probe
- Power outage alarm with optional battery
- EnOcean®-ready: Can be smart-home-enabled for AFRISOhome (can be retrofitted)

Application

For visual and audible alarms if liquids with a flash point of > 55 °C are detected. AFA 11 is suitable for fuel oil, diesel fuel, synthetic fuels (for example, GTL) as per EN 15940 and urea solution 32.5 % as per DIN 70070 (AdBlue). Also suitable for motor oils, gearbox oils, machine oils, hydraulic oils or lubricating oils as well as transformer oils, vegetable oils (for example, HVO), water and other liquids. Application as leak detection system class III as per EN 13160-1/-4 as well as safety device as per worksheet DWA-A 791 and worksheet DWA-A779.

Description

The liquid detector AFA 11 is the successor product of the oil/water alarm unit 3.

The unit in a wall mounting housing triggers visual and audible alarms in the event of accumulations of liquids which can be caused by leaks, backflow, flooding, etc. AFA 11 consists of a control unit with visual/audible alarm, Test and Acknowledge keys, a relay output and a photoelectric probe. The probe is mounted at the lowest point of the area to be monitored. Alarm is triggered when escaped liquid is detected. The audible alarm can be muted with the Acknowledge key. The visual alarm remains active until the leak has been removed. The Test key allows you to simulate an alarm condition in order to perform a function test. The voltage-free relay contact is provided for connection of additional alarm equipment (such as additional alarm unit ZAG 01, horn) or building control technology. The alarm units are suitable for panel mounting with a mounting frame. Power outage alarm: An optional 9 V battery can be connected so that an audible alarm is triggered in the case of power outage. The alarm cannot be acknowledged and is disabled once power is available again.

EnOcean® ready: AFA 11 can be integrated into the AFRISO smart home system or other smart home systems based on EnOcean® wireless by means of the optional wireless module TCM 320. This allows for additional push messages to smartphones or via e-mail (further accessories required).

Technical Specifications

Operating temperature range

Ambient: -10/+60 °C

Probe

L x ø: 33 x 10 mm

Cable length: 10 m

Response level (EN 13160-4): ≥ 4 mm

Supply voltage

AC 100 – 240 V

Nominal power

AC 230 V
1.5 VA

Switching output

Relay contact: 1 x voltage-free changeover contact
Contact rating: max. AC 250 V, 2 A
Contact rating: max. DC 30 V, 2 A

Alarm sound

min. 70 dB(A)

Housing

Wall mounting housing made of impact-resistant plastic (ABS)
W x H x D: 100 x 188 x 65 mm
Weight: 500 g
Degree of protection: IP 30 (EN 60529)

approval

DIBt: Z-65.40-214

Scope of delivery

- Control unit
- photoelectric probe

Option

- EnOcean® wireless module (can be retrofitted)

Options

- EnOcean® wireless module (can be retrofitted)

Versions

			Part no.
liquid detector AFA 11	AC 230 V	●	40890

- in-stock items
- Non-stock items