

# Fuel oil de-aerator FloCo-Top-2CM

The FloCo-Top with an improved ecological balance!



Improved ecological balance thanks to the plastic base housing: Reduced weight, robust and durable!



## Product information



## Your benefits

- + Compact dual float safety system keeps oil foam from escaping
- + Drain system and drain valve for fast and clean filter and burner hose replacement
- + Backflow preventer with integrated pressure relief towards the tank
- + Vacuum gauge indicates when it is time to replace the filter
- + Optimised filter cup with thread and O ring seal
- + Reduced height facilitates installation if mounting space is limited
- + Easy installation with click system and AFRISO universal screw connection or standard screw connection
- + "PROOFED BARRIER" if installed with vent hose
- + Emergency operation of system and function test of anti-siphon valve possible via hose connection at drain valve

## Application

For single-line systems with return line in oil-fired systems for continuous de-aeration. Suitable for fuel oil EL (DIN 51603-1), diesel fuel (EN 590), liquid fuels as per DIN SPEC 51603-6 and DIN/TS 51603-8 (draft) as well as biofuel and biodiesel with a maximum of 30 % FAME

(EN 14214). This product is therefore ideal for all ecologically upgraded fuel oil consuming systems that use the new paraffinic fuels HVO or GTL as an admixture or 100%. Also suitable for use in flood hazard areas and flood risk areas.

