

BUILDING TRUST

EB25 DECLARATION OF PERFORMANCE No. 56542853

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	EB25
2	INTENDED USE/S	Sealants for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for façade; Sealants for exterior and interior applications Part 3: Sealants for sanitary joints; Sealing of joints applied in sanitary areas in the interior of buildings exposed to non-pressurised water
3	MANUFACTURER:	EVERBUILD BUILDING PRODUCTS LTD Site 41, Knowsthorpe Ways, Cross Green Industrial Estate, Leeds, LS9 0SW, UK
4	AUTHORISED REPRESENTATIVE:	Not applicable
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	BS EN 15651-1:2012 and BS EN 15651-3:2012
	Notified body/ies:	2538

7

DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Release of dangerous chemicals	See SDS		
Reaction to fire	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 10%		
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		BS EN 15651- — 1:2012
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%		1.2012
Durability	Pass		
Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Essential Characteristics	Performance		
Release of dangerous chemicals	See SDS		
Reaction to fire	NPD		
Resistance to flow	≤ 3 mm		
Loss of volume	≤ 20%		BS EN 15651-
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%		3:2012
Microbiological Growth	3		-
Durability	Pass		



8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas Function: R&D Manager At Leeds on 26 May 2021 Name : Emma Taylor Function: Product Manager At Leeds on 26 May 2021

The

19

End of information as required by UKCA



BUILDING TRUST

Everbuild Building Product	s LTD, Leeds, UK
DoP No. 56542	2853
BS EN 15651-1	2012
Notified Body	2538
Sealants for non-structural use in the joints in buildings and ped application	-
Release of dangerous chemicals	See SDS
Reaction to fire	NPD
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10%
Tensile properties (ISO10590) at maintained extension after water immersion	NF at 60%
Tensile properties (ISO8340) for non-structural sealants used in joints in cold climate areas (-30°C)	NF at 60%
Durability	Pass
for DoP see www.everbuild.	co.uk/downloads/



	JK 1 21
Everbuild Building P	Products LTD, Leeds, UK
DoP No.	. 56542853
BS EN 15	5651-3:2012
Sealants for non-structural use in the joints in building	
Sealants for non-structural use in the joints in building	
Sealants for non-structural use in the joints in building sanitary areas in the interior of build	gs and pedestrian walkways for sealing of joints applied in dings exposed to non-pressurized water
Sealants for non-structural use in the joints in building sanitary areas in the interior of build Release of dangerous chemicals	gs and pedestrian walkways for sealing of joints applied in dings exposed to non-pressurized water
Sealants for non-structural use in the joints in building sanitary areas in the interior of build Release of dangerous chemicals Reaction to fire	gs and pedestrian walkways for sealing of joints applied in dings exposed to non-pressurized water See SDS NPD
Sealants for non-structural use in the joints in building sanitary areas in the interior of build Release of dangerous chemicals Reaction to fire Resistance to flow	ss and pedestrian walkways for sealing of joints applied in dings exposed to non-pressurized water See SDS NPD ≤ 3 mm
Sealants for non-structural use in the joints in building sanitary areas in the interior of build Release of dangerous chemicals Reaction to fire Resistance to flow Loss of volume Tensile properties (ISO10590) at maintained	ss and pedestrian walkways for sealing of joints applied in dings exposed to non-pressurized water See SDS NPD ≤ 3 mm ≤ 20%

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



