

FEBMIX DH

DECLARATION OF PERFORMANCE

No. 23111266

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	FBMIXDH
2	INTENDED USE/S	Air entraining / plasticizing admixture for masonry mortar
3	MANUFACTURER:	Everbuild Building Products LTD Site 41, Knowsthorpe Way, Cross Green Industrial Estate, LS9 0SW
4	AUTHORISED REPRESENTATIVE:	Not Applicable
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN934-3:2009 +A1:2012
	Notified body/ies:	0086

Declaration of Performance

FBMIXDH
23111266
Jan 2021 , ver. 01
1213

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Chloride ion content	<0.1% w/w		EN934-3:2009
Alkali Content	<5% w/w		
Compressive Strength	≥70% of control		
Corrosive behavior	Contains only components according to EN934-1 annex A.1		
Entrained air	T2(1) Total air content A1 after standard mixing A1 = (17±3)%v/v		
	T2(2) Total air content after 1 hour standing A1 ≥ - 3% v/v		
	T2(3) Total air content after extended mixing ≤A1 + 5% v/v and ≥A1 - 5% v/v		
Dangerous Substances	None (see MSDS)		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
Function: Technical Product Co-ordinator
At Leeds on 07 January 2021



Name :
Function:
At Leeds on 08 January 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

FBMIXDH
23111266
Jan 2021 , ver. 01
1213



Everbuild Building Products LTD, Leeds, UK

DoP No. 23111266

EN934-3:2009 +A1:2012

Notified Body 0086

Air entraining / plasticizing admixture for masonry mortar

Chloride ion content	<0.1% w/w
Alkali Content	<5% w/w
Compressive Strength	≥70% of control
Corrosive behavior	Contains only components according to EN934-1 annex A.1
Entrained air	T2(1) Total air content A1 after standard mixing $A1 = (17 \pm 3)\% \text{ v/v}$ T2(2) Total air content after 1 hour standing $A1 \geq -3\% \text{ v/v}$ T2(3) Total air content after extended mixing $\leq A1 + 5\% \text{ v/v}$ and $\geq A1 - 5\% \text{ v/v}$
Dangerous Substances	None (see MSDS)

For DoP see <https://www.everbuild.co.uk/downloads/>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

FBMIXDH
23111266
Jan 2021 , ver. 01
1213

Declaration of Performance

FBMIXDH

23111266

Jan 2021 , ver. 01

1213

